



SYR Maroon Buffing Floor Pad

TECHNICAL DATA SHEET

1.0 Description

The Maroon Buffing Floor Pad is constructed of synthetic fibres in a textured, non-woven fabrication and is suitable for dry and spray buffing. Abrasive particles are dispersed throughout and bonded to the non-woven construction with a sturdy binder/adhesive and also contains antimicrobial treatment.

2.0 Intended Use

Maroon Floor Pads are used for the maintenance of floor surfaces. The pad cleans the floor when damp, yet buffs when dry. This exceptional Floor Pad will bring out the highest gloss on more buffable floor finishes. Ideal for spray cleaning to remove scuff marks and polishes the floor to a sparkling finish.

Floor pads are intended for use on standard speed rotary floor cleaning machines or automatic scrubber-dryers.

Suitable for use on machine speeds of 175-350 rpm.

3.0 Construction

Made of 100% recycled PET fibres and 100% water based latex resins. Floor pads are designed to be used on both sides.

4.0 Packaging and Marking

Labelling is to clearly identify product and quantity.

5.0 Directions for Use of Floor Pads

Dust mop or sweep floors prior to buffing/stripping. Use pad until soil and finish have been removed from the floor. Pick up cleaning solution with a mop, wet vacuum or automatic scrubber-dryer. Rinse floor and leave to dry or if used dry, vacuum or mop the residue prior to recoating or opening to traffic

6.0 Product Care of Floor Pads

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. Do not clean the pad in a washing machine. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

7.0 Properties

Property	Value	Test Method
Thickness	0.32 – 0.43 in	D5736-95
Weight	653 – 884 g/m ² 19.2 – 26.0 oz/yd ²	D6242-98
Fibre Type	PET 100% Recycled	---
Binder System	Synthetic Blend	---
Binder Application	Spray/Spray	---
Abrasive	Aluminium Oxide	Schieffer Test
Colour	Maroon	---

8.0 Floor Pad Sizes available

From 6" - 21" diameter

9.0 Environmental commitment

PET fibre used in our floor pads comes from 100% post-consumer and industrial recycled waste material.

SYR certification: ISO 9001 Quality Management Systems.

Material manufactured under environmental regulations.

Note: Due to the properties of the material and variable conditions of use, there may be variations in the specifications. Please contact SYR with any questions about the product.

SCOT YOUNG RESEARCH LTD., Lye By-Pass, Lye, Stourbridge, West Midlands DY9 8HG United Kingdom.

T: +44 (0)1384 421421 E: sales@syrcclean.com W: www.syrcclean.com